ROMABIO®

CLASSICO **LIMEWASH®**

for **DISTRESSED LIMEWASH ON BRICK AND STONE**


Classico Limewash in Bianco White // Photo: Kindred Vintage

PRODUCT FEATURES

- Authentic, Italian slaked lime paint used for beautiful, wash-off finishes on brick and stone
- No primer needed on absorbent, unpainted, unsealed natural masonry surfaces
- Easy to use, 1-coat paint process
- Breathable, long-lasting, and patinas over time
- Perfect for PROs and DIYers
- Ideal for Interior fireplaces
- Removable for the first 2 days for a no-stress application
- No odor, Zero-VOC, and environmentally friendly

"I have nothing against natural brick. I think it's beautiful. But I am a sucker for that European lime washed brick."

~ Lauren Shaver, Bless'r House Blog

ROMABIO®

CLASSICO LIMEWASH

for **DISTRESSED LIMEWASH ON BRICK AND STONE**

COLOR PROFILE & BASE TYPE

- Romabio offers seven curated whites and neutrals in the Classico Color Collection including Avorio White (neutral, off-white), Bianco White (pure, cool tone white), Cristallo White (antique, off-white), Nube Gray (subtle, beige-gray), Riposo Beige (light beige), Toscano Beige (soft beige), and Tropea Beige (true beige)
- Offered in White Base only that can be custom tinted light to medium-light colors
- Once dry, finish will be lighter and more opaque

SIZES AVAILABLE

- **1L SKU**: CLW-BIANCO-WB-1L
- **2.5L SKU**: CLW-BIANCO-WB-2.5L
- **15L SKU**: CLW-BIANCO-WB-15L

COVERAGE

- **1L/1 qt.** approximately 80 – 100 sq/ft*
- **2.5L/.67 gal.** approximately 200 – 250 sq/ft*
- **15L/4 gal.** approximately 1,200 – 1,500 sq/ft*

**For 1 coat based on average absorption. Actual coverage will vary based on application method, surface texture, and absorption.*

RECOMMENDED DILUTION

	1L/1QT	2.5L/0.67GAL	15L/4GAL
50%	500mL	1.25L	7.5L
75%	750mL	1.75L	11.25L
100%	1L	2.5L	15L

APPLICATION ON BRICK or STONE

1. Dilute Classico Limewash 50% to a max of 100% with clean water and mix thoroughly before and during use.
2. Dampen the surface before painting for best results.
3. Apply with a Romabio Masonry Brush or an airless sprayer (min 3000psi and tip opening of 0.019”-0.021”).
4. Distress the paint once it starts to dry (within about 30mins). Use a hose or spray bottle with a stiff stream for the most natural look. You can also use a wet cloth or soft brush depending on your desired finish.

Perform a full test of different dilutions and distressing techniques on the smallest wall first until you get the look you want before moving on to the rest of the project.

HELPFUL TIPS

- Test surface with water to check absorption of masonry surface and mortar before applying. If water beads on surface, paint will not absorb properly.
- Paint complete wall from top to bottom to avoid lap lines.
- Only dilute the paint you will use within 5 days. Store remaining paint undiluted.
- Apply when temps are between 50°F and 88°F and avoid full sun if possible.
- Waterproof and extend the life of your finish with Romabio Mineral Shield. Learn more at romabio.com/mineralshield.

TOOLS



Scan to Learn More

ROMABIO is a registered trademark licensed to Romabio Paints, LLC., ©2024 Romabio Paints, LLC

REV022724